

BRIGHT SEAL

High Gloss Floor Sealer

KLEIN & CO
TERRAZZO

Product Description

BRIGHT SEAL is a clear modified acrylic blended in special solvents producing a tough, hard, high gloss finish in one application. Although **BRIGHT SEAL** is a topical sealer, it also functions as a penetrating agent that will enhance and brighten colors of marble, stone, and concrete.

USES

BRIGHT SEAL is designed for use on cement or epoxy terrazzo. It is also suitable for exterior use on a clean dry surface of brick pavers, slate, stone or terra cotta. Recommended for use on exterior rustic terrazzo.

ADVANTAGES

BRIGHT SEAL provides a high gloss finish that is durable and stain resistant. It is not affected by temperature change and may be used with confidence for exterior application. The product may be used over itself to repair worn traffic patterns. **BRIGHT SEAL** is fast drying, slip resistant, and non-yellowing. **BRIGHT SEAL** will preserve deep color tones.

APPLICATION

The applied surface must be clean and dry. If other sealers or cleaning agents have been used, they must be removed or neutralized. The area must be well ventilated.

Apply **BRIGHT SEAL** with long, uniform strokes using a lambs wool applicator, soft brush, or short nap roller. Do not use any sponge type applicator. Leave no puddles. Best results are obtained by allowing 24 hours between applications. Apply to a small area to determine suitability.

LIMITATIONS

BRIGHT SEAL is a solvent (oil) base formula and should not be applied to any polished or pre-sealed surface. It is not intended for use on smooth, dense surfaces similar to quarry tile and ceramics.

Areas of application must be well ventilated (see cautions). Other types of adjoining floor products must be protected, i.e. vinyl, carpet, plastic and wood.

CAUTION

BRIGHT SEAL is a flammable formulation and must be used with care. Before using, extinguish all pilot lights and any other applications that may produce spark. Vapor harmful, use only with adequate ventilation. Protective clothing and eye protection should be provided. In case of eye contact, flush with water. May be harmful or fatal if swallowed. If ingested, DO NOT INDUCE VOMITING. Call a physician at once. See reverse for Material Safety Data Sheet. (MSDS).

CURING CHARACTERISTICS

Drying time less than one hour depending on temperature. Light foot traffic when not tacky. Restrict area for 24 hours. Forced ventilation will reduce vapors.

QUICK REFERENCE

- SOLVENT BASED
- HIGH GLOSS
- QUICK DRYING

ABOUT ACRYLICS

Acrylics are plastics and are soft materials compared to masonry or clay. Acrylic traffic finishes will scratch or dull with time and foot traffic. This is expected. That is why the traffic finishes must be easily repaired— they are easier to repair than abraded tile.

Not all acrylics are the same. There are thousands of possible acrylic formulations and they are all different. For example, the primary sealer is soft to allow for thermal expansion and bonding ability over a wide range of temperature and different tile textures, while the acrylic traffic coating is very hard and scuff resistant. The sealer does not strip with ammonia, but the glossy traffic finish will.

TYPICAL PROPERTIES

TYPE.....AROMATIC XYLENE
SOLIDS25%
D.O.T.....FLAMMABLE LIQUID
APPEARANCE.....CLEAR/ LIGHT AMBER

**FOR PROFESSIONAL
USE ONLY**

KLEIN AND COMPANY, INC.
167 Hickory Springs Industrial Drive
Canton, GA 30115

800.241.0641
GA 770.345.6334
FAX 770.345.6282

Seller Warrants that should this product prove to be defective, it will be replaced or refund will be issued for price of goods. The suitability of a product for an intended use shall be solely up to the user. Seller assumes no liability for consequential damages. Liability shall in no event exceed the purchase price of materials supplied by KCI. No person has the authority to change such terms and there are no warranties except as herein stated.

WWW.KLEINCOINC.COM