

GROUT GUARD® 2

A Grout Release For Brick Pavers and Ceramic Tile

KLEIN & CO
TERRAZZO

Product Description

Grout Guard 2 is an acrylic emulsion of alkali soluble resin that provides for more efficient grout clean up. There are no industry standards for this type of material however, **Grout Guard 2** has been thoroughly field tested and proven since 1978 on millions of square feet or jobsite applications.

USES

Grout Guard 2 is used at the job site in lieu of factory applied paraffin wax. It is intended for use on wire cut pavers or other clay tile units having a textured extruded surfaces.

ADVANTAGES

Eliminates the need for expensive factory waxing. Reduces the amount of grout left on tile surfaces at the time of grouting. **Grout Guard 2** is not harmful to any type of grouting material.

Grout Guard 2 is easy to apply, with no special tools needed. Follow directions on label for application and removal.

Grout Guard 2 provides rapid job progress and scheduling, the floor is left in better condition and call backs are reduced.

APPLICATION

Application is made before any grouting is done and the surface must be clean of any construction debris or setting mortar.

Using a short nap paint roller, apply for faces only of tile or paver. Do not allow excessive run-off into the joint area. Some deep wire-cut paving units may require a second coating, which should be applied in a cross direction. Allow about one hour drying time at 70° F. Protected pavers will have a glazed appearance.

Removal (cleanup) should be performed as soon as possible after grouting has sufficiently cured (see label for additional instruction). Clean up is accomplished with an alkaline solution using 8 oz. of TSP (trisodium phosphate) to one gallon of water or with a warm water pressure washer. *Do not use*

Seller Warrants that should this product prove to be defective, it will be replaced or refund will be issued for price of goods. The suitability of a product for an intended use shall be solely up to the user. Seller assumes no liability for consequential damages. Liability shall in no event exceed the purchase price of materials supplied by KCI. No person has the authority to change such terms and there are no warranties except as herein stated.

LIMITATIONS

Exposure to acid will harden the coatings by temperatures less than 50° F.

The drying time between application and grouting is extended by low temperatures and/or high humidity.

AVAILABILITY

This product is available throughout the U.S.A., Canada, Mexico, Puerto Rico and the Bahamas.

COVERAGE

Varies with texture and absorption of surface. Averages 300 to 600 square.

PACKAGING

GALLONS (6 per case)
5 GALLON PAIL
55 GALLON DRUM

TYPICAL PROPERTIES

TYPE.....SEMI-GEL, TACKY, RESINOUS, WATERABLE EMULSION
D.O.T.....Class 55
WEIGHT/ GALLON.....9 LBS.
pH Factor.....7.5

APPEARANCE:
CLOUDY WHITE

To insure suitability, the user must test this product in a small area before proceeding. Floor special applications. Consult with local distributor or contact KCI Customer Service at 800.241.0641. KEEP AWAY FROM CHILDREN. See attached or visit www.kleincoinc.com for Material Safety Data Sheets (MSDS).

PROTECT FROM FREEZING

KLEIN AND COMPANY, INC.
167 Hickory Springs Industrial Drive
Canton, GA 30115

800.241.0641
GA 770.345.6334
FAX 770.345.6282

WWW.KLEINCOINC.COM