NATURAL STONE

Color Enhancer & Sealer



Product Description

High-Solids, matte finished. Water-based penetrating acrylic-urethane blend.

INSTRUCTIONS

Interior or Exterior

All floor areas must be cleaned and double rinsed to remove all traces of acid wash or other cleaning solutions. If area has been previously treated with any sealer a TEST must be made for compatibility.

APPLICATION

All application tools must be clean and should not have been used for any other products. Application is best made with lambs wool, flat paint pad or soft bristle brush. A roller or spray equipment may be used. Apply a thin even coating leaving NO puddles. Do not apply on any surfaces that is subject to constant wetting. To insure satisfaction, the user should TEST this product in a small area before proceeding

COVERAGE

Coverage will vary depending on the density, porosity, texture, surface absorption, weather and time solution applied on surface and application methods. Used as directed, will cover approximately 250-650 square feet per gallon.

CAUTION

Contains glycol ether and acrylic polymers. Harmful if ingested, DO NOT INDUCE VOMITING. For eye contact flush with clean water. In any case contact physician . Ask for MSDS.

KEEP AWAY FROM CHILDREN

Seller Warrants that should this product prove to be defective, it will be replaced or refund will be issued for price of goods. The suitability of a product for an intended use shall be solely up to the user. Seller assumes no liability for consequential damages. Liability shall in no event exceed the purchase price of materials supplied by KCI. No person has the authority to change such terms and there are no warranties except as herein stated.

KLEIN AND COMPANY, INC. 167 Hickory Springs Industrial Drive Canton, GA 30115

800.241.0641 GA 770.345.6334 FAX 770.345.6282