

PRO-TEC PLUS

Water Based Penetrating Sealer



Product Description

Pro-Tec Plus is a nonflammable, water soluble SODIUM METHYL SILICONATE solution used for water repellency on a variety of surfaces.

USES

Pro-Tec Plus is designed for use on most types of surfaces of natural and pre-cast stone, bricks, clay pavers, porcelain tile and concrete products. Test in a small area to determine compatibility as a grout release. **Pro-Tec Plus** is an excellent treatment for grout joints.

ADVANTAGES

Pro-Tec Plus is vapor permeable, which allows substrate to breathe. It can be applied to damp surfaces allowing immediate application after clean up.

Pro-Tec Plus is suitable for interior and exterior use and retains the natural look of the surface. It forms a water-resist surface within 24 hours after application (5-10 year water repellency on surface).

Reduces the effects of freeze/thaw cycle. Will not discolor or alter color tones. One application only for the best results.

APPLICATION

The applied surface may be damp but not wet. Application is made with garden type sprayer, soft bristle brush or roller. Apply liberally. Wipe up any excess, leave no puddles. Follow directions on label.

PACKAGING

Pro-Tec Plus is available in quarts (12 per case), 5 gallons (6 per case), 55 gallon drums.

LIMITATIONS

Pro-Tec Plus is not recommended for use on polished marble / granite or glazed ceramics. Avoid overlapping or second coating.

Avoid contact with other materials not to be coated. Applied surface must be clean and free of any mortar droppings.

NO other product should be applied prior to application. **Pro-Tec Plus** is an alkaline solution (see caution note). Acid washed floors must be neutralized before application of Klein and Company, Inc. **Pro-Tec Plus**. Ask for MK POWDER (acid neutralizer).

Protect from freezing. Avoid hot surface temperature. Reduce temperature by dampening.

CURING CHARACTERISTICS

Complete curing will usually occur within 24 hours. There is no lingering odor or residue if properly applied.

TYPICAL PROPERTIES

TYPE.....NETRATING METHYL SILICONATE
ALKALINE SOLUTION
D.O.T.....CLASS 55
WEIGHT/GALLON.....9 LBS.

APPEARANCE:

WET.....WATER CLEAR
DRY.....NOT VISIBLE

CAUTION

KLEIN AND COMPANY, INC. PRO-TEC PLUS IS AN ALKALINE SOLUTION AND MUST BE USED WITH CARE. PROTECTIVE CLOTHING AND EYE PROTECTION SHOULD BE PROVIDED. IN CASE OF EYE CONTACT, FLUSH WITH WATER AND GET MEDICAL ATTENTION.

FOR PROFESSIONAL USE ONLY

KLEIN AND COMPANY, INC.
167 Hickory Springs Industrial Drive
Canton, GA 30115

800.241.0641
GA 770.345.6334
FAX 770.345.6282

Seller Warrants that should this product prove to be defective, it will be replaced or refund will be issued for price of goods. The suitability of a product for an intended use shall be solely up to the user. Seller assumes no liability for consequential damages. Liability shall in no event exceed the purchase price of materials supplied by KCI. No person has the authority to change such terms and there are no warranties except as herein stated.